

UHF Side Mounted Dipole Antennas

360-600 MHz

SMD4 Series



The SMD4 series are a range of unity gain side mounted dipoles which can be used as a single antenna for short range applications or, if desired, phased together to provide high gain array coverage characteristics.

The SMD4-67 is of all welded aluminium construction. The feed point is protected by an ABS cap, with the internal PTFE based cable construction providing excellent intermodulation performance (-150dBc).

The stainless steel SMD41-67 is electrically identical to its aluminium counterpart and is recommended for corrosive environments.


The SMD4 Series antennas are supplied with a boom for ¼ wave antenna to mast spacing.




Key Features:

- Versatile - Antennas can be phased and manipulated to achieve a variety of horizontal radiation patterns and varying gains.
- Lightweight - Easily mounted and installed with single clamps
- All welded, full folded dipole construction
- A range of suitable phasing harnesses available
- DC grounded for lightning protection and dissipation of static noise

Typical VSWR Response (SMD4-67-P)



H Plane (SMD4-67-P)



Electrical Specifications

Model Number	SMD4-67-P	SMD41-67-P	SMD4-99-P*	SMD41-99-P*
Nominal Gain dBi (dBd)	Nominally 2 (Unity) but varies with mounting arrangements			
Frequency MHz	400 - 520		360 - 600	
Tuned Bandwidth	Entire band		20.0%	
VSWR (Return Loss)	<1.5:1 (14dB)			
Nominal Impedance Ω	50			
Vertical Beamwidth°	Typically 70 at ¼ λ antenna - mast spacing			
Horizontal Beamwidth°	Typically 220 at ¼ λ antenna - mast spacing			
Input Power W	500			
Passive IM 3rd order dBc	-150	-140	-150	-140

Mechanical Specifications

Model Number	SMD4-67-P	SMD41-67-P	SMD4-99-P*	SMD41-99-P*
Construction	All welded aluminium with alodined finish	Stainless steel	All welded aluminium with alodined finish	Stainless steel
Length m	0.4	0.4	0.5	0.5
Weight kg	0.3	0.6	0.3	0.6
Termination	4.3-10 female with short RG142 cable tail			
Mounting Area	100mm x 25mm diam. alodined aluminium			
Suggested Clamps	1 x UNV			
Projected Area cm ²	No Ice	200		213
	With Ice	423		480
Wind Load (Thrust) @ 160km/h N	24		25	
Wind Gust Rating km/h	>240			
Torque @ 160 km/h Nm	3		5	

* The SMD4-99 is a specific frequency version of the SMD4. This antenna is designed only for use as a single dipole, not as a component of a phased dipole array as the antenna is custom made to user specified frequencies and is not specifically matched to a phasing harness.